

Heizmatte 172-DUSN, 175 W/m², 230 V, IP X7, Heizleiterabstand: 10 cm

RG: 010 | LZ: 1 Woche

Typ	Best.-Nr.	Leistung (W)	Abmessungen (cm)		
			Länge	Breite	m ²
172DUSN040-55	38000	152	160	55	0,8
172DUSN012-55	37998	278	290	55	1,6
172-DUSN1-55	37996	388	400	55	2,2
172-DUSN8-55	37994	565	590	55	3,25
172-DUSN2-55	37992	674	700	55	3,85
172-DUSN3-55	37990	953	990	55	5,45
172-DUSN4-55	37988	1269	1320	55	7,26
172-DUSN5-55	37985	1604	1670	55	9,19
172-DUSN6-55	37981	2268	2360	55	12,98

Typ	Best.-Nr.	Leistung (W)	Abmessungen (cm)		
			Länge	Breite	m ²
172DUSN040-75	37999	152	120	75	0,8
172DUSN012-75	37997	278	210	75	1,6
172-DUSN1-75	37995	388	300	75	2,2
172-DUSN8-75	37993	565	430	75	3,25
172-DUSN2-75	37991	674	510	75	3,85
172-DUSN3-75	37989	953	730	75	5,45
172-DUSN4-75	37987	1269	970	75	7,26
172-DUSN5-75	37983	1604	1220	75	9,19
172-DUSN6-75	37980	2268	1730	75	12,98

Heizmatte 173-DUSN, 175 W/m², 400 V, IP X7, Heizleiterabstand: 10 cm

RG: 010 | LZ: 1 Woche

Typ	Best.-Nr.	Leistung (W)	Abmessungen (cm)		
			Länge	Breite	m ²
173DUSN040-55	37978	265	270	55	1,49
173DUSN012-55	37975	483	500	55	2,75
173-DUSN1-55	37972	675	700	55	3,85
173-DUSN8-55	37969	983	1020	55	5,61
173-DUSN2-55	37966	1172	1220	55	6,71
173-DUSN3-55	37962	1657	1720	55	9,46
173-DUSN4-55	37959	2207	2290	55	12,6
173-DUSN5-55	37955	2789	2900	55	15,95
173-DUSN6-55	37952	3944	4100	55	22,55

Typ	Best.-Nr.	Leistung (W)	Abmessungen (cm)		
			Länge	Breite	m ²
173DUSN040-75	37976	265	200	75	1,49
173DUSN012-75	37973	483	370	75	2,75
173-DUSN1-75	37970	675	510	75	3,85
173-DUSN8-75	37967	983	750	75	5,61
173-DUSN2-75	37964	1172	890	75	6,71
173-DUSN3-75	37961	1657	1260	75	9,46
173-DUSN4-75	37957	2207	1680	75	12,6
173-DUSN5-75	37954	2789	2120	75	15,95
173-DUSN6-75	37951	3944	3000	75	22,55