

## TECHNICAL DATA

- > Operating voltage: 400 V, 3~50Hz
- > Temperature: 30 °C to 60 °C
- > Installation: Wall assembly
- > Water pressure: 1.0 to 10 bar
- > Color: White
- > Protection class: IP 25
- > Protection class: I
- > Water connection: Gz 1/2"
- > Energy efficiency class: A

## PRODUCT ADVANTAGES

- + LC display
- + Temperature setting accurate to the degree
- + 4 switchable power ratings
- + Electronic control
- + Suitable for solar heating up to 60 °C inlet temperature for reheating
- + Maximum temperature interlock
- + Memory function of 3 stored temperatures
- + Easy replacement of old equipment

## APPLICATION

- + from 9 kW: several sinks
- + from 12 kW: shower and sink
- + from 18 kW: bathtub and sink

## AQUA WHL

Electronic instantaneous water heater with LCD



AQUA WHL is a fully electronic instantaneous water heater with LCD and is ideal for heating water in the bathroom.

Thanks to the flow sensor, the instantaneous water heater heats automatically from 0.1 bar and a water flow rate of over 2.5 l/min. The control circuit selects the appropriate heat output from the instantaneous water heater depending on the water withdrawal, desired water temperature and water flow temperature. By means of a simple rotary knob, the inlet and outlet temperature, the flow rate and the power can be selected precisely to the degree desired.

	ET-AQUA-WHL-15	ET-AQUA-WHL-24
Power levels (kW)	9/11/12/15	17/18/21/24
Rated current (A)	3 x 13.0/15.9/17.3/21.7	3 x 24.6/26.0/30.3/34.6
Power cross section (mm <sup>2</sup> )	4 x 1.5/2.5/2.5/2.5	4 x 4/4/4/6
Hot water capacity Δt=30° (L/min)	4,3/5.2/5.8/7.2	8.1/8.7/10.1/11.6

## AQUA WHL, electronic instantaneous water heater with LCD

RG: W1| LZ: ex stock

Type	Art. No.	Power up to (kW)	Width (mm)	Height (mm)	Depth (mm)	Weight (kg)	Price €
ET-AQUA-WHL-15	41109	15	245	440	126	4.85	<b>459.00</b>
ET-AQUA-WHL-24	41110	24	245	440	126	4.85	<b>459.00</b>