

Dipole heating mat 82-RGS, 80 W/m², 230 V, IP X7

RG: 001 | LZ: 1 week

Type	Art. no.	Output (W)	Dimensions (cm)		
			Length	Width	m ²
082-RGS040-65	32638	126	240	65	1.56
082-RGS012-65	32637	230	435	65	2.83
082-RGS1-65	32636	321	615	65	4.00
082-RGS8-65	40868	468	900	65	5.85
082-RGS2-65	33886	558	1080	65	7.02
082-RGS3-65	32635	789	1515	65	9.85
082-RGS4-65	32639	1051	2025	65	13.16
082-RGS5-65	30872	1328	2550	65	16.58
082-RGS6-65	40867	1878	3615	65	23.50

Type	Art. no.	Output (W)	Dimensions (cm)		
			Length	Width	m ²
082-RGS040-105	40857	126	150	105	1.56
082-RGS012-105	40858	230	270	105	2.83
082-RGS1-105	40860	321	375	105	4.00
082-RGS8-105	40861	468	555	105	5.85
082-RGS2-105	40862	558	660	105	7.02
082-RGS3-105	40863	789	945	105	9.85
082-RGS4-105	40864	1051	1245	105	13.16
082-RGS5-105	40865	1328	1575	105	16.58
082-RGS6-105	40866	1878	2235	105	23.50

Dipole heating mat 102-RGS, 100 W/m², 230 V, IP X7

RG: 001 | LZ: 1 week

Type	Art. no.	Output (W)	Dimensions (cm)		
			Length	Width	m ²
102RGS040-65	30105	141	210	65	1.40
102RGS012-65	30584	257	390	65	2.55
102-RGS1-65	30284	359	555	65	3.60
102-RGS8-65	31046	523	810	65	5.25
102-RGS2-65	30995	624	960	65	6.25
102-RGS3-65	30162	882	1350	65	8.80
102-RGS4-65	30970	1175	1800	65	11.75
102-RGS5-65	30355	1485	2280	65	14.85
102-RGS6-65	30971	2100	3225	65	21.00

Type	Art. no.	Output (W)	Dimensions (cm)		
			Length	Width	m ²
102RGS040-105	32663	141	135	105	1.40
102RGS012-105	32678	257	240	105	2.55
102-RGS1-105	32661	359	345	105	3.60
102-RGS8-105	33405	523	495	105	5.25
102-RGS2-105	32674	624	600	105	6.25
102-RGS3-105	29865	882	840	105	8.80
102-RGS4-105	29864	1175	1125	105	11.75
102-RGS5-105	32659	1485	1410	105	14.85
102-RGS6-105	29870	2100	1995	105	21.00

Dipole heating mat 122-RGS, 120 W/m², 230 V, IP X7

RG: 001 | LZ: 1 week

Type	Art. no.	Output (W)	Dimensions (cm)		
			Length	Width	m ²
122-RGS040-65	32991	154	195	65	1.27
122-RGS012-65	32679	282	360	65	2.34
122-RGS1-65	32680	393	510	65	3.32
122-RGS8-65	37494	573	735	65	4.78
122-RGS2-65	37874	683	870	65	5.66
122-RGS3-65	37539	966	1245	65	8.09
122-RGS4-65	37875	1287	1650	65	10.73
122-RGS5-65	37876	1626	2085	65	13.55
122-RGS6-65	37877	2300	2955	65	19.21

Type	Art. no.	Output (W)	Dimensions (cm)		
			Length	Width	m ²
122-RGS040-105	32676	154	120	105	1.27
122-RGS012-105	32675	282	225	105	2.34
122-RGS1-105	37621	393	315	105	3.32
122-RGS8-105	32673	573	450	105	4.78
122-RGS2-105	32672	683	540	105	5.66
122-RGS3-105	32462	966	765	105	8.09
122-RGS4-105	33153	1287	1020	105	10.73
122-RGS5-105	32632	1626	1290	105	13.55
122-RGS6-105	32989	2300	1830	105	19.21

Dipole heating mat 152-RUS, 150 W/m², 230 V, IP X7

RG: 001 | LZ: 1 week

Type	Art. no.	Output (W)	Dimensions (cm)		
			Length	Width	m ²
152RUS040-55	29672	141	170	55	0.95
152RUS012-55	29544	257	310	55	1.70
152-RUS1-55	29521	359	440	55	2.40
152-RUS8-55	29670	523	630	55	3.50
152-RUS2-55	29522	624	760	55	4.15
152-RUS3-55	29523	882	1070	55	5.90
152-RUS4-55	29519	1175	1420	55	7.85
152-RUS5-55	29520	1485	1800	55	9.90
152-RUS6-55	29669	2100	2540	55	14.00

Type	Art. no.	Output (W)	Dimensions (cm)		
			Length	Width	m ²
152RUS040-95	35225	141	100	95	0.95
152RUS012-95	30926	257	180	95	1.70
152-RUS1-95	32409	359	250	95	2.40
152-RUS8-95	32027	523	370	95	3.50
152-RUS2-95	32025	624	440	95	4.15
152-RUS3-95	32482	882	620	95	5.90
152-RUS4-95	32472	1175	820	95	7.85
152-RUS5-95	32479	1485	1040	95	9.90
152-RUS6-95	32493	2100	1470	95	14.00

Accessories for RS heating mats

RG: 008* / 007 | DT: in stock

Type	Art. no.	Description
KALT-RS-1.5	34699	PTC thermistor KALT-RS-1.5 for RS heating mats & RLH heating loop, 2x1.5mm ² , with Aluminium shield + protective conductor
KALT-RS-2.5	34700	PTC thermistor KALT-RS-2.5 for RS heating mats, 2x2.5mm ² , with Aluminium shield + protective conductor
MRS	33335	Repair set MRS, for heating cable of heating mats RS
FSH-20	26881	Sensor protective pipe made of copper for installation pipe DN-20
eTWIST	40517	Switch mounted thermostat with control dial and app function via Bluetooth 4.2, 16 A, 5-28 °C, white
eTOUCH-eco	40511	Switch mounting thermostat with touch pad, 16 A, 5-35 °C, white
eTOUCH wifi	44722	Switch mounting thermostat with touch pad and WLAN function, 16 A, 5-40 °C, white
eTOUCH mini	39300	Switch mounted thermostat with white touch pad, 16 A, 5-40 °C