

Laminotherm LM, 120 W/m², 230 V, IP X7

RG: 003 | DT: ex stock

Type	Art. no.	Output (W)	Length (cm)	Width (cm)	m ²
122-LM5-100	40590	60	100	50	0.5
122-LM5-200	39616	120	200	50	1.0
122-LM5-400	39617	240	400	50	2.0
122-LM5-600	39678	360	600	50	3.0
122-LM5-800	39679	480	800	50	4.0
122-LM5-1000	39680	600	1000	50	5.0
122-LM5-1200	39681	720	1200	50	6.0
122-LM5-1400	39682	840	1400	50	7.0
122-LM5-1600	39683	960	1600	50	8.0
122-LM5-1800	39684	1080	1800	50	9.0
122-LM5-2000	39685	1200	2000	50	10.0

Laminotherm Set LMSU - with a smart switch mounted thermostat eTOUCH eco



eTOUCH eco



Laminotherm



Accessories

- > 1 Laminotherm 122-LM, 120 W/m²
- > 1 x eTOUCH eco switch installation thermostat
- > 1 sensor protective pipe FSH-12
- > 2.5 m of installation pipe SS-12

Laminotherm Set LMSU, 120 W/m², 230 V, IP X7

RG: 003 | DT: ex stock

Type	Art. no.	Output (W)	Length (cm)	Width (cm)	m ²
SET-LMSU5-200	36607	120	200	50	1.0
SET-LMSU5-400	36679	240	400	50	2.0
SET-LMSU5-600	36680	360	600	50	3.0
SET-LMSU5-800	36681	480	800	50	4.0
SET-LMSU5-1000	36682	600	1000	50	5.0
SET-LMSU5-1200	36683	720	1200	50	6.0
SET-LMSU5-1400	36684	840	1400	50	7.0
SET-LMSU5-1600	36685	960	1600	50	8.0
SET-LMSU5-1800	36686	1080	1800	50	9.0
SET-LMSU5-2000	36687	1200	2000	50	10.0

Laminotherm Set LMSS - with electronic switch mounted thermostat eTWIST



eTWIST



Laminotherm



Accessories

- > 1 Laminotherm 122-LM, 120 W/m²
- > 1 switch mounted thermostat eTWIST
- > 1 sensor protective pipe FSH-12
- > 2.5 m of installation pipe SS-12

Laminotherm Set LMSS, 120 W/m², 230 V, IP X7

RG: 003 | DT: ex stock

Type	Art. no.	Output (W)	Length (cm)	Width (cm)	m ²
SET-LMSS5-200	37802	120	200	50	1.0
SET-LMSS5-400	37803	240	400	50	2.0
SET-LMSS5-600	37804	360	600	50	3.0
SET-LMSS5-800	37805	480	800	50	4.0
SET-LMSS5-1000	37806	600	1000	50	5.0
SET-LMSS5-1200	37808	720	1200	50	6.0
SET-LMSS5-1400	37810	840	1400	50	7.0
SET-LMSS5-1600	37811	960	1600	50	8.0
SET-LMSS5-1800	37812	1080	1800	50	9.0
SET-LMSS5-2000	37813	1200	2000	50	10.0

Accessories for Laminotherm heating mats

RG: 007* / 008 | DT: in stock

Type	Art. no.	Description
WAK	28353	Adhesive tape made of aluminium, 50 m roll, width: 50 mm
KRU	27544	Capillary thermostat, switched current 16 A, 10 – 60° C, sensor wire 1.5 m
Laminoflies-10	38553	Aluminium coated impact sound insulation for optimal distribution of heat, 10 m ² /roll, thickness: 3 mm
KALT-DS-1	29851	PTC thermistor for netted heating mat DS, dipole with protective braiding 1.0 mm ² , per meter