ETHERMA PTXS

The linkable foot warming mat



The ETHERMA PTXS is used for local heating under a sitting or standing area. The heating mat is placed on a flat level surface and connected to a 230 V socket with the plug. The surface temperature of approx. 35-45 °C(depending on the surface) creates a pleasant comfortable temperature and prevents feet from being exposed to cold. It is important that the foot warming mat is not covered by insulating objects. The foot warming mat PTXS for laying is robust and comes with a corrugated texture coating. For use indoors such as workstations, workbenches, sales booths, shipping offices, containers, and more. The mat can also be operated in a humid environment.

Please note that the PTXS is not laid out completely and permanently outdoors, but under light roofing.
Use is recommended at an ambient temperature of 0-10 °C.

TECHNICAL DATA

Voltage: 230 VSurface temp: 35-45 °C

> Surface: Grooved structure

> Material: Rubber
> Colour: Black
> Thickness: 10 mm
> Weight: 8.3 kg
> IP rating: IP X7
> IEC protection class: II

Connection cable: 2x50 cm with plug connection
 Connecting cable: 2.5 m EU plug, type C
 System structure: CE compliant

PRODUCT ADVANTAGES

- + Ergonomic doormat
- + Mats can be coupled up to a length of approx. 5 m (8 pcs. with a 16 A fuse)
- + Slip resistant, non-slip
- + Easy cleaning
- + Fire protection class B1
- + Acid and lactic acid resistant

APPLICATION AREAS

To be used for workstations, workbenches, stands, in containers and also for outdoor events such as Christmas markets.

PTXS foot warming mat, 230 V, IP X7, black

RG: M4 | LZ: ex stock

Туре	Art. No.	Output (W)	Voltage (V)	Length (cm)	Width (cm)	Price €
PTXS-3	40493	300	230	100	60	379.40

ETHERMA PA



Heated carpets pleasantly prevent cold floors in the office, at home, behind a sales desk, at the checkout of a supermarket or at an exhibition stand.

TECHNICAL DATA

CE

Voltage: 230 V
Surface temperature: ~35°C
Surface: Loop
Material: 100 % PP
Standard colour: Anthracite
Thickness: 10 mm
IP rating: IP X1

> Safety function: Protective insulation> Connection cable: Plug cable: 2 m with switch

> System structure: CE compliant

PA heating carpet, 230 V, IP X1, anthracite

RG: M4 | LZ: ex stock

Туре	Art. No.	Output (W)	Voltage (V)	Length (cm)	Width (cm)	Price €
PA-1-NA	40853	60	230	40	60	70.60
PA-2-NA	40854	105	230	70	60	76.70
PA-3-NA	40855	150	230	100	60	80.80
PA-4-NA	40856	180	230	80	90	85.30