

# ETHERMA KST

Infrared dark heater



Building-friendly, cost-effective, durable and safe - these are the features of the KST church heating system. Electrical connection via device plug, through-wiring, simple and quick installation without having to open the device, integrated overheating protection with automatic restart. Shatterproof special heating element without glowing heating coil with high heat output, angle plug included in the scope of delivery.

## TECHNICAL DATA

- > Voltage: 230 V
- > Output: 400 W/lfm
- > Heat output: Down and forward
- > Surface temp: 80 °C
- > Colour: Clay brown, RAL 8003
- > Outer body: Vers. Sheet steel
- > Dimensions: 185 mm x 60 mm
- > IP rating: IP 21
- > IEC protection class: I
- > Mark of compliance: ÖVE



### KST with left connection

LZ: 2-3 weeks

Type	Art. No.	Output (W)	Length (mm)	RG	Price €
KST050L	30793	200	500	D3	196.80
KST060L	30891	240	600	D3	209.30
KST070L	30828	280	700	D3	217.70
KST080L	30712	320	800	D3	222.10
KST090L	30820	360	900	D3	238.80
KST100L	30718	400	1000	D3	251.30
KST110L	31082	440	1100	D3	268.40
KST120L	30822	480	1200	D3	276.40
KST130L	30823	520	1300	D3	289.00
KST140L	30824	560	1400	D3	299.60
KST150L	30825	600	1500	D3	308.70
PG-ST	34551	Connecting cable 0.5 m	A9		15.00

### KST with right connection

LZ: 2-3 weeks

Type	Art. No.	Output (W)	Length (mm)	RG	Price €
KST050R	34152	200	500	D3	196.80
KST060R	32335	240	600	D3	209.30
KST070R	32333	280	700	D3	217.70
KST080R	32332	320	800	D3	222.10
KST090R	33053	360	900	D3	238.80
KST100R	31044	400	1000	D3	251.30
KST110R	32334	440	1100	D3	268.40
KST120R	33530	480	1200	D3	276.40
KST130R	32599	520	1300	D3	289.00
KST140R	31639	560	1400	D3	299.60
KST150R	31022	600	1500	D3	308.70
PG-ST	34551	Connecting cable 0.5 m	A9		15.00

### NOTE:

Please observe the minimum distances around the heater according to the installation instructions.

