



TECHNICAL DATA

- > Voltage: 230 V
- > Switching current: 16 A
- > Temp. range: 0 - 60 °C
- > Floor sensor: 3 m (extendible to max. 50 m)
- > Mounting: On standard mounting rail
- > IP rating: IP 30
- > Width: 17 mm (1 TE)
- > Certification: CE compliant

APPLICATION AREA

Manifold thermostat for use in domestic and industrial applications.

ITR-69

Electronic thermostat for manifold installation



The ITR-69 controller is designed for DIN rail mounting, which allows easy installation in the switch cabinet. It has an analog input for temperature sensors, as well as a switching relay. The device is designed for remote control and can be lowered by means of a timer.

Distribution panel thermostat ITR-69, 230 V, IP 30

RG: E2 | LZ: ex stock

Type	Art. No.	Description	Price €
ITR-69	34697	Electronic manifold controller, remote sensor: 3 m, 0 - 60 °C, 16 A, 230 V, temp. lowering at night	143.80
ET-EF-ITR-69	37848	Remote sensor for manifold controller ITR-69, temperature range 0 - 60 °C	43.70

TECHNICAL DATA



- > Voltage: 230 V
- > Switching current: 16 A
- > Mounting: On standard mounting rail
- > Temp. range: -15 to 75 °C
- > Width: 35 mm (2 TE)
- > Floor sensor: 3 m
- > IP rating: IP 20
- > Certification: CE compliant

PRODUCT ADVANTAGES

- + LCD display
- + Compliant with Ecodesign guidelines
- + Temperature drop detection
- + Weekly program
- + Extensive accessories

APPLICATION AREA

Manifold thermostat for use in domestic and industrial applications.

ITR-80

Electronic universal thermostat for manifold installation with digital display



The ITR-80 is a universal thermostat that has four different modes: heating, cooling, industrial or MAX/MIN mode. The unit is universally designed for heating and cooling applications. Various control properties can be influenced via the parameterization. By means of three operating keys, the set point and all parameters of the controller are adjusted.

Distribution panel thermostat ITR-80, 230 V, IP 20

LZ: ex stock

Type	Art. No.	Description	RG	Price €
ITR-80	39334	Electronic universal thermostat for manifold installation with digital display incl. NTC sensor	E2	172.90
ET-EF-7x	37847	Spare sensor, length: 3 m, NTC	A2	35.90
ET-TF-ITR80-AP	39422	Remote temperature sensor incl. casing as room sensor for ITR-80, temp. range -50 °C to 105 °C	A2	47.50
ET-FF-ITR80-HT	39979	High temperature remote sensor for ITR-80, PTC sensor, temp. range 0 °C to 170 °C, length: 3 m	A2	39.10
ET Snubber	30593	Induction suppressor in conjunction with relay/contactor connection, IP 20, 230 V	A2	25.30