

SOLAMAGIC® D3 CEILING INSTALLATION

Premium dark infrared heater with frame



The SOLAMAGIC® D3 recessed ceiling heater enables safe and discreet installation of the premium dark infrared heater in a wide variety of ceiling constructions, but especially in protected outdoor areas and as a zone heater, e.g. in winter gardens. The casing and the frame are made of high quality aluminum. The device is equipped with a Solastar-AL heating element, which, in addition to high efficiency and a very long service life (approx. 5000 operating hours), is particularly impressive due to the low level of residual light. In protected outdoor areas, dark heater allow very flexible use and guarantee constant, pleasant heat zones.

TECHNICAL DATA

- > Voltage: 230 V
- > Heating element: Solastar-AL (NoGlare)
- > Residual light: 1lux/kW/m²
- > Output: 2000 W
- > Colours: White, titanium, nano anthracite
- > IP rating: IP 44
- > Connection cable: 40 cm + 180 cm plug-in cable for connection during installation

PRODUCT ADVANTAGES

- + Hardly any residual light (< 1 lux) due to the innovative "NO GLARE" heating element
- + Can be integrated into ceilings
- + 20° tiltable
- + Space-saving
- + Maximum heat radiation to the front thanks to innovative reflector design
- + Fast heat at the touch of a button
- + Easy installation

SOLAMAGIC®D3 recessed ceiling premium dark infrared heater

RG: R2 | LZ: 3 weeks

Type	Art. No.	Output (W)	Length (mm)		Width (mm)		Depth (mm)		Price €
			With frame	Part	With frame	Part	Installation	Overhang	
SM-D3-2000-D-W	9300188	2000	900	850	370	300	100	31	1160.80
SM-D3-2000-D-T	9300189	2000	900	850	370	300	100	31	1160.80
SM-D3-2000-D-NA	9300190	2000	900	850	370	300	100	31	1160.80

W: white T: titanium NA: nano anthracite



Tilttable up to 20°

Low installation depth

ETHERMA TIP: SOLAMAGIC® replacement tubes can be found on page 45.