

LAVA® FRAME

The infrared heating panel for wall and ceiling installation



LAVA® FRAME is an infrared heating panel that can be installed flush with the ceiling and wall thanks to the installation frame, creating a harmonious room appearance. It is ideal for use in drywall as well as concrete. Thus, the LAVA® infrared heating panel blends even better into the architecture of the room and becomes as good as invisible.

Suitable as full heating or also for heating zones. This not only saves heating costs, but also creates a pleasant, healthy indoor atmosphere.

NOTE

The LAVA®FRAME is delivered without plug and without plug & play connection.

TECHNICAL DATA

- > Voltage: 230 V
- > Output: 350, 500, 740, 750 W
- > Surface temp.: Max. 120 °C at standard internal temp.
- > Surface: Structured surface
- > Frame: Steel casing, white RAL9016
- > Device depth: 22 mm
- > Installation depth: 75 mm
- > IP rating: IP 21
- > Connecting cable: 1 m, 3 x 1.5 mm² without plug
- > Warranty: 5 years

PRODUCT ADVANTAGES

- + Suitable for wall and ceiling installation
- + Installation frame with Easy-Click
- + Flush mounting
- + Easy installation
- + Large infrared radiation surface
- + High radiation effect
- + Maintenance and magnetic field free

SELECTION GUIDE

The selection of the power is based on the heat requirement of the room (H: 2.5 m) and the application of heating. As a guideline:

- 20-45 W/m² Low energy and passive energy house
- 50-70 W/m² Well-insulated living space
- 75-95 W/m² Medium-insulated living space
- 100-120 W/m² Poorly insulated living space

LAVA® FRAME built-in infrared heating panel incl. installation frame, RAL 9016 Traffic white

RG: I2 | LZ: ex stock

Type	Art. No.	Output (W)	Installation dimension (mm)	Dimensions without frame (mm)		Weight without frame (kg)	Price €
				Length	Width		
LAVA-FRAME-350	40505	350	635 x 635 x 75	620	620	7.5	838.30
LAVA-FRAME-500	40506	500	635 x 915 x 75	900	620	12	952.50
LAVA-FRAME-740	44719	700	915 x 915 x 75	900	900	17	1063.90
LAVA-FRAME-750	40507	750	635 x 1260 x 75	1245	620	16	1085.20

Accessories

RG: E1 | LZ: ex stock

Type	Art. No.	Description	Price €
eTWIST-BASIC-1	41278	Switch-mounted thermostat with rotary control and app function via Bluetooth 4.2, 16 A, 5-28 °C, white	124.60
eTOUCH-ECO	40511	Switch-mounted thermostat with touchpad, 16 A, 5-35 °C, white	194.60
ET-14A	40595	Radio room thermostat, LCD display with clock and weekly program	178.30
ET-111A	36758	Radio receiver with 10 A relay in surface-mounted casing	143.50

ETHERMA TIP: Plan your infrared heating panel with ETHERMA ePLANNER at: www.etherma.com/eplanner.